



CASEY EQUIPMENT, LTD

DRILL PIPE SPECS

2-7/8" 10.40# S-135 DRILL PIPE

PIPE BODY O.D.	(in)	2.875
NOMINAL PIPE I.D.	(in)	2.151
NOMINAL WEIGHT		10.40
ADJUSTED WEIGHT	(lbs./ft.)	11.29
PIPE BODY GRADE		S-135
PIPE BODY WALL THICKNESS	(in)	0.3620
API CLASS- TUBE		PREMIUM
PIPE BODY TENSILE	(lbs)	299,800
PIPE BODY TORSIONAL	(ft./ lbs)	15,900
PIPE BODY COLLAPSE	(psi)	25,602
PIPE BODY INTERNAL YIELD/ BURST	(psi)	27,197
PIPE BODY DISPLACEMENT	(gal/ft.)	0.0041
PIPE BODY CAPACITY	(gal/ft.)	0.0043
CONNECTION TYPE		2-7/8" AOH
CONNECTION O.D.	(in)	3.875
CONNECTION I.D.	(in)	2.156
TOOL JOINT DRIFT	(in)	2.031
RECOMMENDED MAKE UP TORQUE	(ft./ lbs)	5,200
MINIMUM MAKE UP TORQUE	(ft./ lbs)	4,300
TOOL JOINT TORSIONAL STRENGTH	(ft./ lbs)	8,700
TOOL JOINT TENSILE STRENGTH	(lbs)	331,700

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hosting capacity, ID coatings, and hardbands are not considered in these figures.

Capacity/ displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates.