



CASEY EQUIPMENT, LTD

DRILL PIPE SPECS

2-3/8" PH6 5.95# P110 TUBING

PIPE BODY O.D.	(in)	2.375
NOMINAL PIPE I.D.	(in)	1.995
NOMINAL WEIGHT		4.700
PIPE BODY GRADE		L80
PIPE BODY WALL THICKNESS	(in)	0.190
API CLASS- TUBE		PREMIUM
PIPE BODY TENSILE	(lbs)	82,019
PIPE BODY COLLAPSE	(psi)	8,952
PIPE BODY INTERNAL YIELD/ BURST	(psi)	10,240
PIPE BODY DISPLACEMENT (INCLUDES TJ)	(gal/ft.)	0.0017
PIPE BODY CAPACITY (INCLUDES TJ)	(gal/ft.)	0.0039
CONNECTION TYPE		2-3/8" EUE
CONNECTION O.D.	(in)	3.063
CONNECTION I.D.	(in)	1.995
TOOL JOINT DRIFT	(in)	1.901
RECOMMENDED MAKE UP TORQUE	(ft./ lbs)	2,250
MAKE UP TORQUE OPTIMAL	(ft./ lbs)	1,800
MINIMUM MAKE UP TORQUE	(ft./ lbs)	1,350

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hosting capacity, ID coatings, and hardbands are not considered in these figures.

Capacity/ displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates.