



CASEY EQUIPMENT, LTD

DRILL PIPE SPECS

2-7/8" EUE 6.50# L80 TUBING

PIPE BODY O.D.	(in)	2.875
NOMINAL PIPE I.D.	(in)	2.441
NOMINAL WEIGHT		6.500
PIPE BODY GRADE		L80
PIPE BODY WALL THICKNESS	(in)	0.217
API CLASS- TUBE		PREMIUM
PIPE BODY TENSILE	(lbs)	114,076
PIPE BODY COLLAPSE	(psi)	8,006
PIPE BODY INTERNAL YIELD/ BURST	(psi)	9,661
PIPE BODY DISPLACEMENT (INCLUDES TJ)	(gal/ft.)	0.0024
PIPE BODY CAPACITY (INCLUDES TJ)	(gal/ft.)	0.0058
CONNECTION TYPE		2-7/8" EUE
CONNECTION O.D.	(in)	3.668
CONNECTION I.D.	(in)	2.441
TOOL JOINT DRIFT	(in)	2.347
RECOMMENDED MAKE UP TORQUE	(ft./ lbs)	2,880
MAKE UP TORQUE OPTIMAL	(ft./ lbs)	2,300
MINIMUM MAKE UP TORQUE	(ft./ lbs)	1,730

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hosting capacity, ID coatings, and hardbands are not considered in these figures.

Capacity/ displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates.