



# CASEY EQUIPMENT, LTD

## DRILL PIPE SPECS

### 3-1/2" EUE 9.30# L80 TUBING

PIPE BODY O.D.	(in)	3.500
NOMINAL PIPE I.D.	(in)	2.992
NOMINAL WEIGHT		9.300
PIPE BODY GRADE		L80
PIPE BODY WALL THICKNESS	(in)	0.254
API CLASS- TUBE		PREMIUM
PIPE BODY TENSILE	(lbs)	163,178
PIPE BODY COLLAPSE	(psi)	7,399
PIPE BODY INTERNAL YIELD/ BURST	(psi)	9,289
PIPE BODY DISPLACEMENT (INCLUDES TJ)	(gal/ft.)	0.0034
PIPE BODY CAPACITY (INCLUDES TJ)	(gal/ft.)	0.0087
CONNECTION TYPE		3-1/2" EUE
CONNECTION O.D.	(in)	4.500
CONNECTION I.D.	(in)	2.992
TOOL JOINT DRIFT	(in)	2.867
RECOMMENDED MAKE UP TORQUE	(ft./ lbs)	4,000
MAKE UP TORQUE OPTIMAL	(ft./ lbs)	3,200
MINIMUM MAKE UP TORQUE	(ft./ lbs)	2,400

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hosting capacity, ID coatings, and hardbands are not considered in these figures.

Capacity/ displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates.