



CASEY EQUIPMENT, LTD

DRILL PIPE SPECS

4-1/2" PH6 15.50# P110 TUBING

PIPE BODY O.D.	(in)	4.500
NOMINAL PIPE I.D.	(in)	3.826
NOMINAL WEIGHT		15.500
PIPE BODY GRADE		P110
PIPE BODY WALL THICKNESS	(in)	0.337
API CLASS- TUBE		PREMIUM
PIPE BODY TENSILE	(lbs)	388,000
PIPE BODY COLLAPSE	(psi)	11,472
PIPE BODY INTERNAL YIELD/ BURST	(psi)	11,536
CONNECTION TYPE		4-1/2" PH6
CONNECTION O.D.	(in)	5.125
CONNECTION I.D.	(in)	3.765
TOOL JOINT DRIFT	(in)	3.701
RECOMMENDED MAKE UP TORQUE	(ft./ lbs)	9,375
MAKE UP TORQUE OPTIMAL	(ft./ lbs)	8,438
MINIMUM MAKE UP TORQUE	(ft./ lbs)	7,500

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hosting capacity, ID coatings, and hardbands are not considered in these figures.

Capacity/ displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates.